



Technical Specifications

BRAND & MODEL	CHL CPCD70	
MAIN		
Rated Capacity	kg	7000
Load Centre	mm	600
Mast Type	Duplex 2-Stage Mast	
Max Lifting Height	mm	4000
Fork Length	mm	2000
Tyres (Front / Rear)	Solid Tyres (4-8.25-15-14PR / 2-8.25-15-14PR)	
DIMENSIONS & WEIGHT		
Total Weight	kg	9170
Overall Width	mm	1995
Mast Min Height	mm	3050
Canopy Height	mm	2450
Ground Clearance	mm	200
Mast Tilt Angle	(°)	6 / 12
Fork Width Adj. Range (Max / Min)	mm	1845 / 300
Min Turning Radius (Ext / Int)	mm	3360 / 200
Right Angle Stacking Aisle Width	mm	3040
PERFORMANCE		
Max Travel Speed (Load / No Load)	km/h	26 / 28
Lifting Speed (Load / No Load)	mm/s	480 / 560
Lowering Speed (Load / No Load)	mm/s	480 / 560
Max Traction (Load / No Load)	kN	54 / 54
Max Gradeability (Load / No Load)	(%)	20 / 30
ENGINE		
Make & Model	MITSUBISHI S6S-T	
Fuel Type	Diesel ASTM No.2	
Battery x Quantity	80AH x2	
Fuel Tank Capacity	L	90
Rated Power	kW/rpm	82.3/2000
Rated Torque	Nm/rpm	416/1400-1600

