



Choon Huat
Engineering Pte Ltd



I'VE GOT THE POWER2GO

Your Mobile Power Station

Your perfect companion on construction sites or for outdoor activities. Robust design and functionality characterize the POWER2GO WORK.



Handle/protective
frame/versatile
stand functions

Power Switch
ON/OFF

SOC display/
charging status

230 VAC
outlet with cover



FRONT VIEW

Handle/protective
frame/versatile
stand functions

DC-IN MPPT
Charging via solar panel

AC-IN
Charging via grid



BACK VIEW



Solar Charging Option

ENQUIRE NOW

✉ sales@choonhuat.com.sg

☎ (65) 6862 2222





TECHNICAL DETAILS

Basic parameters	POWER2GO WORK
Cell chemistry	Lithium-ion
Capacity	2,500 Wh
Nominal power	2,500 W
Max. power	3,600 W
Output voltage	230 V / 50 Hz
Charging voltage	100-250 V 50/60 Hz
Charging power	1,000 W
Output socket	Continental majority std. (2x)
Input socket	C14 connector
Weight	~25 kg
Dimensions	531 x 233 x 467 mm incl. handle
Degree of protection	IP65 all cover closed
Operating temperature	-10 °C – 60 °C
Charging temperature	0 °C – 45 °C
Certification	UN 38.3, CE
Indicators	LED indicator
Enclosure type	Aluminum
Accessories	
MPPT	30-60Vdc; 8.5A
Solar panel	< 500 W