## **TOWER LIGHT**





## **Technical Specifications**

BRAND & MODEL	CH-GEN TOWER LIGHT 4 x 400W LED			
LED LIGHT				
Lumens	lm	60,000		
Lux @ 10M distance	lux (Eavg/ Emax)	380 / 588		
LED Type	BRIDGELUX / PHILLIPS			
LED Angle	(°)	60		
Driver	MEANWELL			
GENERATOR				
Make & Model	CH-GEN CHDG-5SPK			
Fuel Tank Capacity	L	15		
Fuel Consumption	L/Hr	0.65		
Diesel Generator Capacity	kVA	4.5 / 5.0 (Single Phase)		
Frequency	Hz	50 / 60		
Starting System	Battery			
Weight	kg	350		
Sound Level (at 7m)	db(A)	68		
UNIT				
Dimension (L x W x H)	mm	1250 x 700 x2350		
Max Height	mm	3800		

## PL/40L & 1KL (5KVA) – Enhancement Features

No.	CH-GEN Enhancement Design	Other Brand Design
1	Protection Rack - Protect the body of generator and allow to fix additional items such as drip tray, swivel wheel etc.	
	CHOOM MUAT  DRP TRAY	Bohc
2	Built-in drip tray - To contain any spills and leaks from the engine.	
	- Allows easy housekeeping & convenient for lifting.	
	IS/395 LEIM 10	LUG7500S SUPER SILENT DIESEL GENERATOR

No.	CH-GEN Enhancement Design	Other Brand Design
3	Swivel wheels with built in brake feature From unidirectional to 360° directional Able to move the generator to smaller locations more easily.	Other Brand Design
	DRIP TRAY	PIKO GO
4	Enlarged engine oil capacity - Enables longer maintenance intervals, e.g. 30 -45 days.	
	- Do not have to top up engine oil every 1-2 weeks.	
		G 2 1 S

No.	CH-GEN Enhancement Design	Other Brand Design
5	Steel fuel tank net filter - Extended fuel tank net filter to trap more contaminant while maintaining visibility of fuel oil level in the tank; to allow longer maintenance periods Enables longer maintenance intervals	
6	Fuel-water separator filter in diesel main line	
	- The original small filter gets choked quickly, therefore requires more frequent maintenance Fuel-water separator serves to separate water and dirt from fuel that is entering the engine Enables longer maintenance intervals.	



