

I'VE GOT THE POWER2GO

Your Mobile Power Station



E-Mobility



Drive
System



Energy Storage
Systems



Power and
Garden Tools



Industrial



Medical

NO SOCKET? NO PROBLEM!

For our smartphones, we often reach for the power bank in our private lives. But what if more power is needed? Let's think bigger! **POWER2GO** is designed for demanding users. The dustproof and waterproof **POWER2GO** energy storage system is also a robust companion for all occasions.

Is it heavy to carry? Not at all!

Can you carry it single-handedly? Absolutely!

POWER2GO impresses with its extremely high power density and weighs only 23 kg! It replaces your stationary power connection. Devices with up to 3,600 W peak power can be easily operated with **POWER2GO**.









Consistent, long-term power output of 2,500 W.

All of this is offered by **POWER2GO**, your reliable power network on the go.

Your advantages:

- IP 65
- Rechargeable with solar cells
- High installed energy capacity – 2.5 kWh
- Long operating time between charging cycle
- Fully charged in 2.5 hours
- Low noise – no fan

Operating time*

	10W	15.000 min
	65W	2.280 min
	420W	360 min
	800W	200 min
	1.000W	150 min
	1.200W	124 min
	1.200W	125 min
	2.200W	70 min

* Average values



SOLAR PANEL IN A BUNDLE

Inexhaustible power? No Problem!

With our foldable solar panels, you can charge your **POWER2GO** wherever there is sunlight – while camping, at construction site, or at home in the garden.

So you're using green electricity and doing something good for the environment.



TECHNICAL DETAILS



Basic parameters		POWER2GO WORK
Cell chemistry		Lithium-ion
Capacity		2,500 Wh
Nominal power		2,500 W
Max. power		3,600 W
Output voltage		230 V / 50 Hz
Charging voltage		100-250 V 50/60 Hz
Charging power		1,000 W
Output socket		Continental majority std. (2x)
Input socket		C14 connector
Weight		~25 kg
Dimensions		531 x 233 x 467 mm incl. handle
Degree of protection		IP65 all cover closed
Operating temperature		-10 °C – 60 °C
Charging temperature		0 °C – 45 °C
Certification		UN 38.3, CE
Indicators		LED indicator
Enclosure type		Aluminum
Accessories		
MPPT		30-60Vdc; 8.5A
Solar panel		< 500 W

POWER2GO WORK

Your perfect companion on construction sites
or for outdoor activities. Robust design and
functionality characterize the POWER2GO WORK.



Handle/protective
frame/versatile
stand functions

Power Switch
ON/OFF

SOC display/
charging status

230 VAC outlet
with cover

FRONT VIEW



Handle/protective
frame/versatile
stand functions

DC-IN MPPT
charging via solar panel

AC-IN
charging via grid

REAR VIE

Any questions?

Contact us, we will be pleased to advise you.



Choon Huat
Engineering Pte Ltd

For Sales Enquiries, please contact us at:

Email: sales@choonhuat.com.sg

Tel: (65) 6862 2222